

Examples of **paresse** package usage.

le TEXnicien de surface

2004-04-17

This file loads the **amsmath** package and, if it locally exists, the **lmodern** package.

With the macro `\ActiveLaParesse` to make the § character active.

```
{\ActiveLaParesse
  (\$a^{\$b}_{\$g}) and also (\$D^{\$a}_{\$d})
}
```

to obtain : α_γ^β and also Δ_δ^α

With the environment **ParesseActive**.

```
\begin{ParesseActive}\large
\begin{tabular}{*4{||>{\ttfamily \$}c|c}||} \hline
a & \$a & b & \$b & g & \$g & d & \$d\\ \hline
e & \$e & z & \$z & h & \$h & v & \$v\\ \hline
...
X & \$X & P & \$P & S & \$S & U & \$U\\ \hline
F & \$F & Q & \$Q & W & \$W &\multicolumn{2}{c}{}\\ \hline
\end{tabular}
\end{ParesseActive}
```

§a	α	§b	β	§g	γ	§d	δ
§e	ε	§z	ζ	§h	η	§v	θ
§i	ι	§k	κ	§l	λ	§m	μ
§n	ν	§x	ξ	§p	π	§r	ρ
§s	σ	§y	τ	§u	υ	§f	φ
§c	χ	§q	ψ	§w	ω		
§G	Γ	§D	Δ	§V	Θ	§L	Λ
§X	Ξ	§P	Π	§S	Σ	§U	Υ
§F	Φ	§Q	Ψ	§W	Ω		